

## AVAILABILITY

C'2c/Classic	C'2s/Classic	C'2ms/Classic	C'2c/Core	C'2s/Core	C'2m/Core
-	-	•	-	-	•

## OPTIONS ACCESSORIES

High feet	
Milk container 2 x 4.5 Liter	•
Decorative technical panel	

# SPECIFICATIONS

Dimensions (W/H/D): 300 x 603 x 600 mm (11.81 x 23.74 x 23.62 in)
Weight: 33 kg
Internal fridge volume: 13 L
Milk container - 1 milk type container: 9 L
Milk container - 2 milk types container (option): $2 \times 4.5 L$
Storage for up to: 24 espresso cups
Power consumption: 75 W (cup heater on) /45 W (cup heater off) (for Europe)
Refrigerant: R600a
Thermostat: Digital with temperature display
Installation specifications: Setup on the right side of the Cameo
Locking system: Key

Eversys S.A. T&C apply. Prices are ex-factory Sierre (Switzerland), VAT not included, without transport insurance. Prices are subject to change.

Although the information in this price list is presented in good faith and believed to be correct at the time of publishing, Eversys SA makes no rep-

resentations or warranties as to the completeness or accuracy of the information. Eversys SA has no liability for any errors or omissions in the materials.



C'fridge beneath ■



## AVAILABILITY

C'2c/ST	C'2s/ST	C'2ms/ST	C'2c/Classic	C'2s/Classic	C'2ms/Classic	C'2c/Core	C'2s/Core	C'2m/Core
-	-	•	-	-	•	-	-	•

## OPTIONS ACCESSORIES

Milk container 2 x 2 Liter

## SPECIFICATIONS

Installation specifications: Setup beneath the Cameo

Dimensions (W/H/D): 430 x 210 x 600 mm (16.93 x 8.26 x 23.62 in)
Weight: 22 kg
Internal fridge volume: 11 L
Milk container - 1 milk type container: 5.5 L
Milk container - 2 milk types containers (option): 2 x 2 L
Power consumption: 45 W (for Europe)
Refrigerant: R600a
Thermostat: Digital with temperature display
Locking system: None



# AVAILABILITY

C'2c/Classic	C'2s/Classic	C'2ms/Classic	C'2c/Core	C'2s/Core	C'2m/Core
•	•	•	•	•	•

### OPTIONS ACCESSORIES

High feet

Lockable Lids

Decorative technical panel

### SPECIFICATIONS

Dimensions (W/H/D): 230 x 582 x 600 mm (9.05 x 22.91 x 23.62 in)

Weight: 23 kg

Powder containers: 2 x 1.5 kg

Hardware configuration: Cameo pre-configuration necessary

Mechanical configuration: C'choco predisposition mandatory on coffee machine, coffee outlet V2 (metal) and CPU V2

Software: V2.5x and higher

Voltage: 24 V provided by the Cameo (for Europe)

Installation specifications: Only setup on the left side of the Cameo. For use with Cameo machines only



### AVAILABILITY

C'2c/Classic	C'2s/Classic	C'2ms/Classic	C'2c/Core	C'2s/Core	C'2m/Core
•	•	•	•	•	•

### OPTIONS ACCESSORIES

High feet

# SPECIFICATIONS

Dimensions (W/H/D): 300 x 574 x 600 mm (11.81 x 22.60 x 23.62 in)

Weight: 28 kg

Heatable levels: Four

Removable drawers: Three inox drawers

Storage for up to: 180 espresso cups

Power consumption: 160 W (40 W per level) (for Europe)

Installation specifications: Setup on the right or on the left side of the Cameo



EVERSYS

